










Tabla de compatibilidades de válvulas, colectores y actuadores

VÁLVULA	ACTUADOR			M28		M28		M28		M28		M30		M30		M30	
	HZ1 771 250 230 V 3 puntos	HZ1 771 211 24 V, 0-10 V 2/3 puntos	HZ1 771 225 230 V 3 puntos	HZ1 771 227 24 V, 0-10 V 2/3 puntos	151 610 350 230 V bidireccional	151 610 324 24 V bidireccional	151 610 502 230 V unidireccional	HZ1 742 006 Regulación 20-50 °C	HZ1 742 100 Regulación 40-70 °C	151 600 530 230 V Con micro	HZ1 771 112 24 V	HZ1 771 125 24 V 0-10 V	S00 130 228 230 V	151 600 530 230 V Con micro	HZ1 771 122 24 V	HZ1 771 125 24 V 0-10 V	S00 130 231 230 V
 HZ1 776 138 HZ1 776 139 HZ1 776 140 HZ1 776 141							✓	✓	✓	✓	✓						
 HZ1 403 715 HZ1 403 720 HZ1 403 725 HZ1 403 732 HZ1 403 740 HZ1 403 750	✓	✓															
 HZ1 213 701 HZ1 213 702 HZ1 213 703 HZ1 213 704 HZ1 213 705 HZ1 213 706			✓	✓													
 HZ1 772 311 HZ1 772 302 HZ1 772 303							✓	✓	✓	✓	✓						
 144 601 220 144 601 225 144 601 232					✓	✓	✓										
 143 601 320 143 601 325					✓	✓											
 HZ1 776 101 HZ1 776 102							✓	✓	✓	✓	✓						
 122 600 603 122 600 604 122 600 605 122 600 606 122 600 607 122 600 608 122 600 609 122 600 610 122 600 611 122 600 612													✓	✓	✓	✓	✓
 120 600 203 120 600 204 120 600 205 120 600 206 120 600 207 120 600 208 120 600 209 120 600 210 120 600 211 120 600 212										✓	✓	✓	✓				